

FEDERAL SIGNAL CORP SIGNAL DIV
MR. LEONARD STEINBEIGLE
2645 FEDERAL SIGNAL DR
UNIVERSITY PARK IL 60466

Your most recent Certification is shown below. Please review the text and contact the Customer Service Professional who assisted with your project if revisions are required.

To view your company's current Listing Information or for ordering Listing Information in the 3 x 5-inch card format, please refer to www.ul.com.

UEES
Visual-signal Appliances

December 11, 2007

FEDERAL SIGNAL CORP SIGNAL DIV
2645 FEDERAL SIGNAL DR, UNIVERSITY PARK IL 60466

E162485

Audible-visual signaling appliances Rated Type 3R, Model(s) AV1*, AV1-LED*, AV1-ST*.
Beacon lighting systems Rated Type 1, Model(s) LSHLS-024 (c), LSHLS-120 (c), LSHLS-240 (c), LSHLS-LED-024 (c), LSHLS-LED-120 (c).
Flashing beacon lights Rated Type 3R, Model(s) 141*.
Rotating beacon lights Rated Type 4X and IP66, Model(s) 121*, 121A*, 121S*, 225*, 371*, 371L*.
Stackable beacon lighting systems Rated Type 1, Model(s) Litestak (b).
Strobe lights Rated Type 3R, Model(s) 131DST*, 131ST*, 141ST*, VALS*.
Strobe lights Rated Type 4X, Model(s) LP1*, LP6*.
Strobe lights Rated Type 4X and IP55, Model(s) LP3T (a)*.
Strobe lights Rated Type 4X and IP66, Model(s) FB24ST*, FB2PST*, FB2PSTI*, LP3E (a)*, LP3M (a)*, LP3P (a)*, LP3S (a)*.
(a) - May be followed by I or L, may be followed by additional suffixes.
(b) - Consisting of Base modules: LSB, LSB-120, LSBS; Light modules: LSLD-024, -120, LSL-024, -120, -240 followed by -A, -B, -C, -G or -R. Intended for indoor use only.
(c) - May be followed by -A, -B, -C, -G or R. Intended for indoor use only.
* - Intended for indoor or outdoor use.
Note - All strobes and beacon lights are for general signaling use only, not for fire alarm use.

LOOK FOR LISTING MARK ON PRODUCT

